PIGSTICK

MFL · 22Hz ELF · Geophone. Wireless Pig Tracking Made Easy



No apps to install. No Bluetooth pairing headaches.
No internet required.

Just connect to PigStick's WiFi hotspot, open your web browser, and start tracking.

Dual Detection

Automatically trigger on 22Hz ELF transmitters, MFL inspection tools, or both simultaneously.

Live Mag and Audio Streaming

Listen to and watch tool passages in real-time including on-screen mag and audio waveform displays with pig speed estimation from weld-strikes.

Manned or Unmanned Operation

Stay with it or leave PigStick on-site. The device records 20 seconds before and after every event - no operator required.

One-Tap Reports and Deliverables

Export runs as CSV, PDF, or PNG, or download the full job as a ZIP with mag waveforms, reports, and playable WAV audio files of the passages.



More...

- Works with any device: iPhone, Android, Windows, Mac, Linux.
- Three capture modes: Zero Crossing, Threshold, or Both simultaneously.
- GPS timestamped passage recordings with millisecond precision.
- Data can be used to drive CDI's GlobalTrack live-tracking.
- Over-the-air firmware updates forever. No wires, no hassle, no charge.
- Supports 2 simultaneous client connections.
- Industrial temperature range of -40°C to +80°C.
- USB-C rechargeable battery with week-long life.
- *Swamp/submersible sensor module coming in 2026.*



CDI

1801 N Juniper Ave, Broken Arrow, OK 74012 · +1-918-258-6068 · sales@pigging.com · www.pigging.com