

SeaKing
SEVEN HUNDRED

10K PSI OPEN-FACE SeaKing™ 700 Dry-Mate Underwater Connectors


10K PSI / 700 Bar / 7000m open-face or mated, dual O-ring equipped, high-density, high-voltage, fiber optic and hybrid electrical/optical subsea connectors

SeaKing is an innovative underwater connector series that eliminates a broad range of mechanical design weaknesses found in many of today's high-pressure subsea connector families. From its double O-ring seals and retractable engaging nut, to its multi-keyed mating interface, the SeaKing underwater connector represents a far more reliable approach to subsea power and signal connectivity.


Ideally suited for deep water offshore oil & gas, military/defense, oceanographic research, and other harsh-environment subsea applications, the dry-mate connector series is built for optimal durability and reliability. Tested to 15,000 PSI (open face and mated), and equipped with integrated dual O-ring seals, marine bronze coupling nuts, corrosion-resistant stainless steel shells and high-pressure contact inserts with gold-plated signal contacts, special RF and fiber optic solutions, the Series 700 SeaKing is today's most advanced high-density signal and standard-density power underwater connector.

- High density, small form-factor connector
- Dual O-ring seals ensure high-pressure performance for every leak path
- Signal, power, RF and optical insert arrangements
- Stainless steel with anti-galling marine bronze engaging nut, or cathodic delamination-free PEEK
- Full-mate inspection ports
- Easy O-ring replacement
- Key and keyway polarization


STANDARD CONFIGURATIONS



Cable Connector Plug (CCP)



Bulkhead Connector Receptacle (BCR)



Flange Connector Receptacle (FCR)